

# Stand-Alone Windows® Based Thin Clients

## TeleCLIENT TC7050

*Stand-Alone Windows®-Based Thin Clients*

- Fast, Powerful 1GHz CPU
- Windows CE.Net Operating System
- Wireless LAN and Terminal Emulations Available
- Compact and Energy Efficient Design
- Includes TeleManager Management Software





# TeleCLIENT TC7050

## Stand-Alone Windows® Based Thin Clients

- Fanless, diskless design, with no moving parts to repair
- High data security and virus resistant
- Energy efficient
- Lower Total Cost of Ownership
- Rapid deployment of applications

### TECHNICAL SPECIFICATIONS

#### MODELS

**TC7050** 1GHZ CPU  
**TC7050I** With terminal emulation  
**TC7050 L** - with wireless 802.11b LAN  
**TC7050 Li** - with wireless 802.11b LAN,  
and terminal emulations

#### HARDWARE

##### CPU

Transmeta Crusoe 1GHz x86-base CPU

##### RAM Memory

128MB RAM

##### Flash Memory

32MB Flash

##### Graphics Support

SMI 712 2D Display Controller

##### Resolution Support

Up to 1280x1024 resolution @ 24bit color

##### Audio Support

NS Audio Codec LM4546 with full  
16-bit stereo sound audio out  
8-bit Mic in

##### Device Ports

2 USB, 2 Serial, 1 Parallel, 2 PS/2 1 keyboard  
and 1 mouse included  
Audio ports - 1 Microphone in, 1 audio out

#### NETWORKING & COMMUNICATIONS

##### Networking Protocols

10/100 BaseT Ethernet, Wireless LAN  
IEEE 802.11b\*, TCP/IP, DNS, DHCP, PPP, SNMP,  
SNTP, PPTP, VPN, WakeOn LAN

#### SOFTWARE

##### Client Operating Systems

Windows CE .Net 4.2

##### Server Operating Systems and Software

Microsoft Windows 2003 Server,  
Windows 2000 Server,  
Citrix MetaFrame XP,  
TeleManager Management Software

##### Software Add Ons

Microsoft RDP 5  
Citrix ICA 8

##### Pericom teemtalk 2000 emulations\*

TeleVideo 910, 925, 950, 955  
Digital VT52, 100, 220, 320, 420, 520  
IBM 3151, 3270E, 5250E  
Hewlett Packard 2392A, 2622A, 700/92  
Wyse 50, 50+, 60  
SCO Consol,  
ANSI-BBS  
AixTerm,  
AT38,  
ADDS A2  
Hazeltine 1500

##### New Moon Canaverall 2.1

Air-Fortress Client  
Microsoft Internet Explorer 6.0  
Microsoft Media Player 5.0  
TeleSmart Smart Card\*  
Thin Print

#### ENVIRONMENTAL

##### Operating temperature

32°F to 104°F (0° to 40° C)

##### Storage temperature

-4°F to 140°F (-20° to 60°C)

##### Humidity

20% to 85% non condensing

##### Operating altitude

0 to 10,000 feet (3048 meters)

#### PHYSICAL SPECIFICATIONS

Height: 10.2 inches (25.9cm)  
Width: 4.5 inches (11.4cm)  
Depth: 9.3 inches (23.6cm)  
Weight: 4.2 lbs (1.9kg)

#### POWER

100-240VAC at 50/60Hz, 20W nominal,  
external power supply

#### REGULATORY COMPLIANCE

FCC Class B CE

#### WARRANTY

1 year standard  
2 year additional with online registration

\* Represents Optional

##### TeleVideo, Inc.

2345 Harris Way,  
San Jose, CA 95131  
Tel: 408.954.8333  
Fax: 408.954.0623

[www.televideo.com](http://www.televideo.com)  
[info@televideo.com](mailto:info@televideo.com)

##### Sales

[telesales@televideo.com](mailto:telesales@televideo.com)

##### Technical Support

[ts\\_support@televideo.com](mailto:ts_support@televideo.com)  
Tel: 408.955.7711



New Moon Canaverall iQ™  
from Tarantella®



The TeleVideo name and logo are registered trademarks. All other names referenced are the service mark, trademark or registered trademarks of their respective owners. All specifications are subject to change without prior notice. TeleVideo reserves the right to change specifications without notice. TeleVideo is not liable for any information, typographical errors or omissions. Printed in USA Copyright 2002 TeleVideo, Inc.

Microsoft, Windows, and Windows NT, CE, XP are registered trademarks of Microsoft Corporation. Citrix, WinFrame, MetaFrame, NFuse, and ICA are registered trademarks of Citrix Systems, Inc. All other products are trademarks and/or registered trademarks of their respective companies. \*Optional